


High Voltage Clamp Ammeter | 255A/B

255 series high voltage clamp ammeters can measure up to 69kV high voltage line current and leakage current. 255 comes with an insulation rod, allowing professional users to check status of lightning arresters. The wireless model (255B) is also able to wirelessly transmit data in real-time up to 30m range. Its clamp can be

Advanced



Features :

- Auto range, 2 times/s sampling rate
- Peak hold, Automatic plug clamp
- Manual range/stores 99 sets of data
- RS-232 interface, Data hold
- Auto power off, LCD backlight



Specifications :

Model Selection	Range	255A	255B
Auto Range		√	
Jaw Size		33mm	
Leakage Current (A)	0.01mA~100A	± (1%+5)	± (1%+5)
	100A~600A	± (2%+5)	± (2%+5)
	Voltage (Freq.) 0V~69kV (50Hz/60Hz)	√	√
Other Features			
Display Mode (4 Digits LCD)		√	
Wireless Transmission (≤30m)		√	
Data Recall		√	
Data Storage		99 Data Sets	
Peak Value		√	
LCD Backlight		√	
Data Hold		√	
Auto Power Off		√	
Low Battery Indication		√	
Over-Range Display		√	
Test Mode (Clamp Ct, Integration)		√	
Sampling Rate (About 2 Times/s)		√	
RS-232		√	-
Category Safety Ratings		CAT III 600V	
General Characteristics			
Power		1.5V AAA Battery x 4	
Display		47mm x 28.5mm	
Product Net Weight		335g	
Product Size		68mm x 245mm x 40mm	
Standard Accessories		Batteries, Insulation Rod, Receiver (255B)	