



CS4MXi

**Sharp and fast signal response
with lightning recovery time**

The CS4MXi operates on the famed C.Scope 17kHz frequency operating system developed by C.Scope together with detector enthusiasts specifically for European and UK soil and mineralisation types.

Benefitting from new generation signal processing and filtering the 4MXi produces a superb **sharp and fast signal response with a lightning recovery time**.

The CS4MXi features the option of **three interchangeable heads to enable deeper detection, greater ground coverage and optimised performance for a variety of situations**. Two of these are 2D elliptical and one concentric. The CS4MXi is supplied as standard with the 8 x 11" elliptical search head. Check out the deals on extra heads – you will be surprised how generous we can be.

The CS4MXi has an **Auto and Variable Ground Exclude Control** for more precise ground elimination on mineralised sites.

The CS4MXi has **Two Discriminate Controls** for an instant comparison and analysis of signals. Discriminate 1 can be set low to eliminate iron and Discriminate 2 set high to still accept small hammered silver. There is also a **Pinpoint Function** which switches off the motion effect so that the search head can be brought to rest over the exact target location.

Designed and manufactured in the UK - the quality, ruggedness and perfect lightweight balance of the CS4MXi is second to none. This quality is allied to C.Scope's legendary customer service and an unequalled warranty.

8" concentric Polo
search head



2D elliptical
search head
8 x 11"



AS STANDARD

2D elliptical
search head
11 X 14"



CS4MXi SPECIFICATION

WEIGHT 1.45 kg including batteries

FREQUENCY 17 kHz

MODE Motion

On/Off Sensitivity
Two channel discrimination adjustable settings
Default Auto Ground Balance setting
Manual adjustable Ground Balance setting
Pinpoint switch.

POWER 8 Alkaline 1.5 volt AA or rechargeable NiMH pack.
Battery life approximately 50 hours.
Waterproof sealed battery compartment with easy fit large knurled nut locking.

INTERCHANGEABLE LIGHTWEIGHT SEARCH HEADS
8" (20cm) concentric - available as OPTION
8 x 11" (20 x 28cm) elliptical 2D - supplied as STANDARD
11 x 14" (28 x 34cm) elliptical 2D - available as OPTION

CONTROL BOX in rugged pressure tested ABS moulding.
Hipmount facility.

TWO PART STEM with cam knurled nut locking and hole and pin alignment and length adjustment. GRP lower stem with ultra strong bolt to the search head.

CS6MXi SPECIFICATION

WEIGHT 1.45 kg including batteries

FREQUENCY 17 kHz

MODE Motion

On/Off Sensitivity
Discrimination adjustable setting
Multi tone discrimination in all metal mode
Microprocessor filtering, analysis and processing of signals
Iron Volume
Disc Volume
Default Auto Ground Balance setting
Manual adjustable Ground Balance setting
Pinpoint switch.

POWER 8 Alkaline 1.5 volt AA or rechargeable NiMH pack.
Battery life approximately 30 hours.
Waterproof sealed battery compartment with easy fit large knurled nut locking.

INTERCHANGEABLE LIGHTWEIGHT SEARCH HEADS
8" (20cm) concentric - available as OPTION
8 x 11" (20 x 28cm) elliptical 2D - supplied as STANDARD
11 x 14" (28 x 34cm) elliptical 2D - available as OPTION

CONTROL BOX in rugged pressure tested ABS moulding.
Hipmount facility.

TWO PART STEM with cam knurled nut locking and hole and pin alignment and length adjustment. GRP lower stem with ultra strong bolt to the search head.

C.SCOPE

C.SCOPE INTERNATIONAL LTD
KINGSNORTH TECHNOLOGY PARK
WOTTON ROAD
ASHFORD
KENT
TN23 6LN

TELEPHONE +44(0)1233 629181
FAX +44(0)1233 645897
EMAIL: info@cscope.co.uk

 **STANLAY**™

Asian Contec Ltd.

B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Tel : +91-11-41860000 (100 Lines), Direct Sales Helpline : +91-11-41406926

Fax : +91-11-41860066, Web : www.stanlay.in, email: sales@stanlay.com