LUX Meter | 381



381 lux meter is a professional dedicated compact digital light meter. 381 Light meter measure light intensity and display results in Lux or FC. It has a high sampling rate of 100/s. 381's low power consumption allows up to 200 hours of continuous operation. Results can be stored within the device and transferred to PC for further analysis, printing and storage.

Specifications:

| · | | |
|-------------------------|---------------------|----------|
| Measurements | Resolution | Accuracy |
| Auto Range | $\sqrt{}$ | |
| Display Count | 2000 | |
| | 20 Lux | ±(3%+20) |
| Illuminance Measurement | 200 Lux | ±(3%+8) |
| (Lux) | 2000 Lux | ±(3%+8) |
| | 20000 Lux | ±(3%+8) |
| | 2 Fc | |
| Illuminance Measurement | 20 Fc | |
| (Fc) | 200 Fc | |
| | 2000 Fc | |
| Other Features | | |
| MAX/MIN Mode | $\sqrt{}$ | |
| Data Hold | $\sqrt{}$ | |
| Auto Power Off | $\sqrt{}$ | |
| Low Battery Indication | | |
| Data Storage | 2044 Data Sets | |
| Auto Record Time Setup | $\sqrt{}$ | |
| Real-Time Clock | $\sqrt{}$ | |
| General Characteristics | | |
| Power | 9V Battery (6LF22) | |
| Display | 22.5mm x 32.5mm | |
| Product Net Weight | 185g | |
| Product Size | 195mm x 45mm x 26mm | |





EN55024



371 non-contact tachometers measure rotating speed of shaft or disc with a point laser and reflective tape on the object being measured. These meters can output RPM or count readouts without interfering with the equipment being measured. Specifications:



| specifications. | | | | |
|------------------------------|--|--------------|--|--|
| Measurements | Range | 371 | | |
| Display Count | 100000 | | | |
| RPM Range | 10RPM~99RPM | ±(0.03%) | | |
| | 100RPM~999RPM | ±(0.04%+2) | | |
| | 1000RPM~9999RPM | ±(0.04%+2) | | |
| | 10000RPM~9999RPM | ±(0.04%+2) | | |
| Counts | Range: 0~9999 | J | | |
| | Max. Input Frequency: 10kHz; Bandwidth: 5% | | | |
| Target Distance | 50mm~200mm | \checkmark | | |
| Other Features | | | | |
| Data Hold | $\sqrt{}$ | | | |
| Auto Power Off | $\sqrt{}$ | | | |
| Low Battery Indication ≤4.8V | $\sqrt{}$ | | | |
| MAX/MIN/AVG Mode | $\sqrt{}$ | | | |
| General Characteristics | | | | |
| Power | 1.5V Battery (LR6) X 4 | | | |
| Display | 53mm x 41mm | | | |
| Product Net Weight | 100g | | | |
| Product Size | 184mm x 56mm x 34mm | | | |
| Standard Accessories | Reflective Tape | | | |



Asian Contec Ltd.

Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos.: Tel: +91-11-41860000 (100 Lines), Direct Sales Helpline: +91-11-41406926

Web: www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices: • Faridabad • Mumbai • Bengaluru • Hyderabad • Bhubaneshwar • Guwahati

