

Large Jaws Leakage Current Clamp Meter | 253 A/B



Advanced

253 series large current high precision leakage clamp meters that can measure up to 2000A. These are great solutions for professionals checking insulation effects of motors and identifying leakage power for distribution systems. Its large 80mm x 80mm jaw is able to clamp up to 96mm cables or flat-steel ground wires. 253's intelligent design can measure leakage current, three-phase voltages and display them on the screen simultaneously.

Features :

- Auto range, 2/s sampling rate
- Peak test, LCD backlight, Auto power off
- RS-232 interface, Data hold
- Overload protection, low battery indication



Complies to:
IEC1010-1
IEC1010-2-032



Specifications :

Model Selection	Range	253A	253B
Leakage Current (A)	0mA~300A	±(1.5%+3)	±(1.5%+3)
	300A~1200A	±(2%+3)	±(2%+3)
	1200A~2000A	-	±(3%+3)
	Voltage (Freq.)	√	√
	Resolution	0.01mA	0.1mA
AC Voltage (V)	0.00V~600V	±(1.5%+3)	±(1.5%+3)
	Frequency: 50Hz/60Hz	√	√
	Resolution	0.01V	0.01V
Other Features			
Display Mode	128 Dots x 64 Dots LCD		
Clamp Size	80mm x 80mm		
Data Logging	200 Data Sets		
Test Mode (Clamp Ct, Integration)	√		
Category Safety Ratings	CAT III 600V		
General Characteristics			
Power	1.5V Battery (LR6) x 4		
Display	43mm x 29mm		
Product Net Weight	1kg		
Product Size	275mm x 145mm x 40mm		
Standard Accessories	Batteries, Test Leads (3 Red, 1 Black), Rs-232 Interface Cable, PC Software CD		



Asian Contec Ltd.

Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos. : Tel : +91-11-41860000 (100 Lines), Direct Sales Helpline : +91-11-41406926

Web : www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices : • Faridabad • Mumbai • Bengaluru • Hyderabad • Bhubaneshwar • Guwahati

Quality Management System



ISO 9001: 2015

1-QSC202101102



Ref:ST/253A/B/2021