

ZX3 & ZX5-DL

**Thickness Gauges
Performance & Simplicity!**



Highlights:

- Powered by: 120MHz FPGA timing
- 150 volt square wave pulser
- Pulse-echo measurement
- Adjustable gain (40-52dB), in 3dB steps (vlow, low, med, high, vhi)
- Selectable manual or auto zero
- High speed scan mode
- Dual element transducers (1-10MHz options)
- Low temperature custom LCD display (-22 F / -30C)
- USB-C connectivity (ZX5-DL)
- CDC compatible serial over USB. Optional serial RS232 or bluetooth module (ZX5-DL)
- Data Storage: 32 megabit flash memory (ZX5-DL)
- IP65 protection rating
- 5 year limited warranty

ZX-3 & ZX5-DL Thickness Gauge



The ZX series of thickness gauges offer a performance solution built to withstand the roughest industry conditions. The features included in the ZX Series offer a quality tool that will meet or exceed your application requirements. Our 5 year limited warranty indicates how we feel about the reliability and durability of the ZX Series gauges.

ZX5-DL Additionally provides all of the above features plus Datalogging which server useful in **material condition assessment** when doing audits.

Applications:

- Corrosion & Pitting
- Tube & Pipe
- Tanks
- Boilers
- Glass
- Variety of Applications

SPECIFICATIONS

Physical

Weight:
11 ounces (with batteries).

Size:
Width (2.5 in / 63.5 mm)
Height (5.17 in / 131.3 mm)
Depth (1.24 in / 31.5 mm)

Operating Temperature:
-22 to 167F (-30 to 75C).

Case:
Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed).

Keypad

Sealed membrane that is resistant to both water and petroleum products.

Nine tactile-feedback keys.

Transducer

Dual-element (transmit and receive).

1 to 10 MHz frequency range.

Locking quick disconnect LEMO connectors.

4 foot cable.

Custom transducers available for special applications.

Warranty

5 year limited.



Dakota NDT
an Elcometer company

Power Source

Two 1.5V alkaline, 1.2V NiCad, or 1.5V Lithium AA cells.

Typically operates for 45 hours on alkaline and 23 hours on NiCad.

Low battery indicator on display. Auto shut-off after 5 minutes of inactivity.

Line power USB-C connected to PC or power adapter (ZX5 series).

Display

Multi-function 7 segment 4.5 digit liquid crystal display with 0.500 in digit height. Two 0.125 in 14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes.

Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options.

Bar graph indicates stability of reading.

Data

Sequential data storage, 40 files of 250 readings per file, for 10,000 readings (ZX-5 DL).

Software

Comes complete with USB download cable (ZX-5 DL). No software required, comma separated file type (.csv).

Certification

Factory calibration traceable to NIST & MIL-STD-45662A.

Measuring

Range:
Measures from 0.025 to 36.00 inches (0.63 to 914.4 millimeters). Range dependent on material and transducer type.

Units: English & Metric

Resolution:
0.001 inches (0.01 millimeters)

Velocity Range:
0.0120 to .7300 in/ μ s (305 to 18,542 m/sec)

PRF: 200Hz

Display Update Rate: 10Hz

Gain: 40-52dB range in 3dB steps.

Features

Zero:
Manual or auto zero option.

Probe Diameter:
Selectable probe diameter for improved linearity.

High Speed Scan:
Display the lowest reading found during a scan. Scan speed at 100Hz.

Differential Mode:
Display the +/- difference from a nominal value entered (ZX5-DL).

Alarm Mode:
High & low alarm limits with audible and visual indicators (ZX5 DL).

VX velocity:
Measure in terms of velocity for nodularity testing (ZX5-DL).

REPLACEMENT

Zx3 replaces ZX-3
ZX5-DL replaces ZX-5 DL

Made by Dakota NDT, USA