Palm Size Digital Multimeter | 33D+



The new generation 33+ multimeter series redefines the performance standards for entry-level digital multimeters. The 33+ multimeters can withstand 2 meters drop. 2 Model option include 33A+ AC/DC volt & current multimeter with Auto ranging & an additional 2mF capacitance test (33A+); The second model option 33D+ provides manual ranging AC/DC voltage & DC current with NCV feature non-contact voltage (NCV) test (33D+)



Large LCD screen & clear display, direct readout



Display all range symbols & units, effectively reducing errors



Powered by 2 AAA batteries, economic & easy to obtain



Equipped with 2 thermistors & protective circuits, replaced with ceramic fuses to enhance safety



Upgraded with electromagnetic buzzer; dial select & button audio indication



Convex dial for user friendly range switching



Thick cover with probe slots, ergonomic design & 2m drop proof



Longer and thicker plastic stand. durable & convenient to read data



Complies to: EN61010-1 EN61010-2-030 EN61326





Specifications:

Model Selection	33D+
Range Selection	Manual
Display Count	2000
Measurements	
DC Voltage (V)	200mV/2V/20V/200V/600V
Accuracy	±(0.5%+2)
AC Voltage(V)	200V/600V
Accuracy	± (1.2%+3)
DC Current (A)	2000μA/20mA/200mA/10A
Accuracy	±(1%+2)
AC Current (A)	-
Accuracy	-
Resistance (Ω)	200/2K/20K/200K/20M/200M
Accuracy	±(0.8%+2)
Capacitance (in F)	-
Accuracy	-
Diode Test / Continuity	
Display	
Auto Power Off	
Auto Backlight Off	$\sqrt{}$
Other Features	
Buzzer	$\sqrt{}$
Drop Test	2m
Test Probe Holder	\downarrow
NCV	$\sqrt{}$
Category Safety Ratings	EN 61010-1, EN 61010-2-030 : 2010, EN 61236 : 2013 , CAT II 600V
General Characteristics	
Weight	206g
Size	134mm x 77 mm x 47mm
Power	1.5V Battery (AAA) x 2
Display	66mm x 51 mm
Standard Accessories	Batteries, Test Leads

Features:

- Clear LCD display
- Comfortable protective cover, with test leadhanging groove
- 2 meters drop test, precision protection
- Loud buzzer sound















Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos.: Tel: +91-11-41860000 (100 Lines), Direct Sales Helpline: +91-11-41406926

Web: www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices: • Faridabad • Mumbai • Bengaluru • Hyderabad • Bhubaneshwar • Guwahati