

Palm Size Digital Multimeter | 33A+/D+



Economy

The new generation 33+ multimeter series redefines the performance standards for entry-level digital multimeters. The 33+ multimeters can withstand 2 meters drop. 2 Model option include 33A+ AC/DC volt & current multimeter with Auto ranging & an additional 2mF capacitance test (33A+); The second model option 33D+ provides manual ranging AC/DC voltage & DC current with NCV feature non-contact voltage (NCV) test (33D+)



Large LCD screen & clear display, direct readout



Display all range symbols & units, effectively reducing errors



Powered by 2 AAA batteries, economic & easy to obtain



Equipped with 2 thermistors & protective circuits, replaced with ceramic fuses to enhance safety



Convex dial for user friendly range switching



Thick cover with probe slots, ergonomic design & 2m drop proof



Longer and thicker plastic stand, durable & convenient to read data



Upgraded with electromagnetic buzzer; dial select & button audio indication



Specifications:


Model Selection	33A+	33D+
Range Selection	Auto	Manual
Display Count	2000	
Measurements		
DC Voltage (V)	200mV/2V/20V/200V/600V	
Accuracy	±(0.5%+2)	
AC Voltage(V)	200mV/2V/20V/200V/600V	200V/600V
Accuracy	± (0.7%+3)	± (1.2%+3)
DC Current (A)	200µA/2000µA/20mA/200mA/2A/10A	2000µA/20mA/200mA/10A
Accuracy	±(1%+2)	
AC Current (A)	200µA/2000µA/20mA/200mA/2A/10A	-
Accuracy	±(1.2%+3)	
Resistance (Ω)	200/2K/20K/200K/2M/20M/200M	200/2K/20K/200K/20M/200M
Accuracy	±(0.8%+2)	
Capacitance (in F)	2n/20n/200n/2u/20n/200u/2m	-
Accuracy	±(4%+8)	
Diode Test / Continuity	√	
Display		
Auto Power Off	√	
Auto Backlight Off	√	
Other Features		
Buzzer	√	
Drop Test	2m	
Test Probe Holder	√	
NCV	-	√
Category Safety Ratings	EN 61010-1, EN 61010-2-030 : 2010, EN 61236 : 2013 , CAT II 600V	
General Characteristics		
Weight	206g	
Size	134mm x 77 mm x 47mm	
Power	1.5V Battery (AAA) x 2	
Display	66mm x 51 mm	
Standard Accessories	Batteries, Test Leads	

Complies to:
EN61010-1
EN61010-2-030
EN61326



Features:

- Clear LCD display
- Comfortable protective cover, with test leadhanging groove
- 2 meters drop test, precision protection
- Loud buzzer sound



Asian Contec Ltd.

Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos. : Tel : +91-11-41860000 (100 Lines), Direct Sales Helpline : +91-11-41406926

Web : www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices : • Faridabad • Mumbai • Bengaluru • Hyderabad • Bhubaneshwar • Guwahati

Quality Management System

ISO 9001:2015

#1-QSC202101102



IAS

Ref:ST/33A+D+/2021