

STABILIZED LIGHT SOURCE

Rugged

Durable and compact

Stable

Provides a stable light source

Adaptable

Interfaces to all industry standard connectors

FEATURES:

- Dual and triple lasers available
- 270Hz, 1kHz and 2kHz tone
- Out of band testing at 1625nm and 1650nm
- PC flat polish interface

SPECIFICATIONS

MODEL	SLS520	SLS525	SLS530	SLS535	SLS536
Wavelength (±20nm)	1310/1550	850/1300	1310/1490/1550	1310/1550/1625	1310/1550/1650
Range of Use	Singlemode	Multimode (62.5/125)		Singlemode	
Emitter Type	FP	LED		FP	
Spectrum Width	≤5nm	+/-40nm		≤5nm	
Output Power	≥0dBm/-1dBm	-20dBm/-21dBm		≥0dBm/-1dBm	
Output Power Stability	±0.05dB/15 min ±0.10dB/8hr	±0.05dB/15 min ±0.10dB/8hr		±0.05dB/15 min ±0.10dB/8hr	
MOD Frequency	270, 1kHz, 2kHz				
Display	LCD				
Battery life	60 Hours				
Connector Type	SC/PC (Interchangeable LC, ST, FC)				
Power Supply	9V Alkaline or 1000mAh Lithium Battery/ 9V AC adapter				
Operating Temp.	-10°C to 50°C				
Storage Temp.	-20°C to 70°C				
Relative Humidity	0 to 95% (non-condensing)				
Weight	0.71 lbs (300g)				
Dimension (H×W×T)	6.1 × 3.5 × 1.3" (155 × 89 × 33mm)				
IP Rating	IP54				
Vibration	5Hz to 150Hz, Amplitude = 0.15mm				
Shock	Peak acceleration 25g at a pulse duration of 6ms				
Compliance	CE, FCC, 21 CFR 1040.10 (Laser)				

Specification subject to change without notice.



1390 Aspen Way Vista, CA • 92081

Latin America Phone : 1.760.510.0558

EMEA Phone : +44 (0) 1633927050

©2020 Tempo Inc. • An ISO 9001 Company

Asian Contec Ltd.

Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos.: Tel : +91-11-41860000 (100 Lines),

Direct Sales Helpline : +91-11-41406926

Web : www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices : • Faridabad • Lucknow • Mumbai • Ahmedabad • Bengaluru

• Hyderabad • Bhubaneswar • Guwahati

TempoCom.com | tel 800.642.2155