RPIC1 Ruggedized Industrial Video Drain/Pipe Inspection Camera



with 20/30/40m length options I 5.2mm Ø rod I camera 23mm Ø

Professional pipe video inspection camera designed for inspection of sewer, water, drain & pipe, air ducts, underground cable pipes, etc. equipped with a 23mm dia Sony camera head with 120° view angle, 20-40m fiberglass rod cable and 7" LCD monitor with SD card recording, it's a designed for traversing pipe of diameter **DN 30mm~150mm** & pass through 90 bends in pipes of dia 45mm or higher

Features:

- Snapshot, video & audio recording
- Self leveling camera , Image always upright
- Stainless steel camera head, IP68 waterproof level
- Sapphire glass lens cover, 12 High light white LEDs
- Wireless keyboard for data entry
- Two plastic guides for camera head Ø46mm and Ø80mm allows to push into pipes of dia 40 to 150mm
- 7" LCD color monitor
- SD card slot to store still pictures or videos
- One push record button
- Built in distance Meter count encoder
- Rechargeable battery lasts up to 6 hours
- Ability to go through 90° bends in 45mm dia pipes
- With smart braking system

Functions:

Industrial Video Drain/Pipe Inspection Camera | RPIC1



- Metal sun visor
- easy to operate 7" monitor with DVR and built-in Li-battery
- **6** Fiberglass rod cable Dia. 5.2mm Length: 20/30/40m
- ④ Smart braking system
- **5** Stainless steel camera head, CMOS, waterproof up to 2 bars
- 6 Removable rugged box with keyboard
- Durable metal frame
- **(3)** Army level robust waterproof suitcase







RPIC1 Ruggedized Industrial Video Drain/Pipe Inspection Camera



with 20/30/40m length options I 5.2mm Ø rod I camera 23mm Ø

Specifications:

Suitable for Pipe, Inner dia	Ø30mm to Ø150mm
Traverse through 90° bends of dia	45mm or higher
Camera Head	
Self-leveling Camera	Yes
Camera Head Size	Ø23mm* 45mm (Main body)
Camera Type	Sony CMOS, 420 TV-lines
View Angle	120°
Focus Distance	20cm
Front Lens	Sapphire Glass
Waterproof, Environmental Rating	IP68 Up to 20m under water
LED's	12 High bright LEDs
Camera Material	Stainless Steel #304
Roller Skid	Mini roller skid dia 46mmUniversal Roller skid dia 80mm
Cable Wheel	
Rod Material	Fiberglass rod
Wheel Material	Stainless steel wheel
Rod Length options	20m, 30m or 40m
Distance meter count	Built in encoder
Rotation (on screen display)	Slip Ring
Rod Diameter	Ø5.2mm
LCD Display and DVR	
LCD Size	7-inch 16:9 Super bright HD color LCD screen
LCD Resolution	800 x 480 pixel
LCD Resolution Mirror and Flip	800 x 480 pixel Support image mirror and flip
LCD Resolution Mirror and Flip Video Resolution	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max.
LCD Resolution Mirror and Flip Video Resolution Video Encoding	800 x 480 pixel Support image mirror and flip
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry)	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes TV and Audio Output
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes TV and Audio Output SD Card (up to 32GB)
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory Data Output	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes Yes State Yes Yes Yes Yes Yes Yes Yes Yes Yes USB 2.0 to PC
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory Data Output LED driver	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory Data Output LED driver Playback	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory Data Output LED driver Playback Language	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer
LCD Resolution Mirror and Flip Video Resolution Video Encoding Wireless Keyboard (For Data entry) Monitor Installation Photograph / Snapshot Video & Audio Recording Output External Memory Data Output LED driver Playback Language General Characteristic	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio English + 8 Languages
LCD ResolutionMirror and FlipVideo ResolutionVideo EncodingWireless Keyboard (For Data entry)Monitor InstallationPhotograph / SnapshotVideo & Audio RecordingOutputExternal MemoryData OutputLED driverPlaybackLanguageGeneral CharacteristicPower Supply	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio English + 8 Languages 12V DC charger
LCD ResolutionMirror and FlipVideo ResolutionVideo EncodingWireless Keyboard (For Data entry)Monitor InstallationPhotograph / SnapshotVideo & Audio RecordingOutputExternal MemoryData OutputLED driverPlaybackLanguageGeneral CharacteristicPower SupplyBattery Capacity	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio English + 8 Languages 12V DC charger Li-on battery, 5200mAH, 7.4V
LCD ResolutionMirror and FlipVideo ResolutionVideo EncodingWireless Keyboard (For Data entry)Monitor InstallationPhotograph / SnapshotVideo & Audio RecordingOutputExternal MemoryData OutputLED driverPlaybackLanguageGeneral CharacteristicPower SupplyBattery CapacityOperating Time	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio English + 8 Languages 12V DC charger Li-on battery, 5200mAH, 7.4V 5 hours
LCD ResolutionMirror and FlipVideo ResolutionVideo EncodingWireless Keyboard (For Data entry)Monitor InstallationPhotograph / SnapshotVideo & Audio RecordingOutputExternal MemoryData OutputLED driverPlaybackLanguageGeneral CharacteristicPower SupplyBattery Capacity	800 x 480 pixel Support image mirror and flip PAL 720 x 576 25fps Max. H.264 Yes N/A Yes TV and Audio Output SD Card (up to 32GB) USB 2.0 to PC Built in dimmer Photo, Video and Audio English + 8 Languages 12V DC charger Li-on battery, 5200mAH, 7.4V

Standard Kit







Control Box Camera Head Cable Reel

Screw Driver Car Charger

Power Connection Adaptor Cable

Optiona



Built in 512Hz sonde