

LV Digital Insulation Tester 1KV| SIT500



The **STANONE SIT500 Insulation Tester** is used to measure the insulation resistance of **electrical equipment & household appliances**. This is done by measuring the insulation resistance between **electrical circuits** or **between circuits & ground**. These are ideal tools for ensuring **transformers, generators, high voltage motors, power capacitors, power cables, arresters & other electrical equipment** that can operate in a safe & accurate manner.

It is used for insulation resistance measurement for insulation materials & various kinds of **electric equipment's** such as **transformer, electric machines, cables, switches, electrical appliances**, an ideal tool for electric **maintenance, testing & inspection**.



Complies to:
IEC61010-1

Features :

- 2000 count LCD display, overload indication, backlight
- AC voltage measurement, auto power off
- Auto discharge
- Continuous measurements mode, red warning light and buzzer function

Specifications :

Auto Range	√		
Display Count	2000		
Measurements		Range	Accuracy
Insulation Resistance (Ω)	Test Voltages	100V/250V/500V/1000V	0%~10%
	100V	0MΩ~100MΩ	±(3%+5)
	250V	0MΩ~99.9MΩ	±(3%+5)
		100MΩ~5GΩ	±(5%+5)
	500V	0MΩ~99.9MΩ	±(3%+5)
		100MΩ~5GΩ	±(5%+5)
	1000V	0MΩ~99.9MΩ	±(3%+5)
		100MΩ~5GΩ	±(5%+5)
	Load Current	50V (R=50kΩ) 1mA	0%~10%
		100V (R=100kΩ) 1mA	0%~10%
		250V (R=250kΩ) 1mA	0%~10%
		500V (R=500kΩ) 1mA	0%~10%
		1000V (R=1MΩ) 1mA	0%~10%
Short Circuit Current	—		<2mA
AC Voltage (V)	30V~750V		±(2%+3)
Other Features			
Low Battery Indication	√		
LCD Backlight/Light Alarm	√		
Buzzer Alarm/High Voltage Indication	√		
Overload Indication/Auto Discharge	√		
Test Voltage Secondary Display	√		
Category Safety Ratings	CAT III 600V		
General Characteristics			
Power	1.5V Battery (LR6) x 6		
Display	70.6mm x 34mm		
Product Net Weight	500g		
Product Size	150mm x 100mm x 71mm		
Standard Accessories	Batteries, Test Leads, Alligator Clips, Gallus		



Asian Contec Ltd.

Asian Center, B-28, Okhla Industrial Area, Phase-1, New Delhi -110020, India.

Contact Nos. : Tel : +91-11-41860000 (100 Lines), Direct Sales Helpline : +91-11-41406926

Web : www.stanlay.in www.stanlay.com email: sales@stanlay.com

Regional Offices : • Faridabad • Mumbai • Bengaluru • Hyderabad • Bhubaneshwar • Guwahati

Quality
Management
System

ISO 9001:2015

#1-QSC20201102



Ref: ST/SIT500/2023